

# Face Recognition-Based Smart Attendance System

Prof. Vidya Rajput<sup>1</sup>, Budgude Omkar<sup>2</sup>, Wagh Vaishnav<sup>3</sup>, Raturaj Jagtap<sup>4</sup>, Jadhav Amey<sup>5</sup>

<sup>1,2,3,4,5</sup>Department of Artificial Intelligence and Machine Learning Navsahyadri Education Society's Group of Institutions Savitribai Phule Pune University, Pune, Maharashtra, India

---

## ABSTRACT

The Face Recognition-Based Smart Attendance System provides a smart, automated, and contactless solution for attendance management. Traditional approaches, such as manual attendance systems or RFID, are inefficient and prone to proxy attendance. This specific project uses computer vision technology to detect people and automatically record their attendance in real-time. By using OpenCV for detection and algorithms such as LBPH and CNN for extraction, faces are matched to a pre-trained database. The attendance is marked in a secure database, and an admin panel is also provided for reporting. Experimental results show that the system is accurate even with the presence of different lighting conditions and angles, thus making it less administrative and proxy-proof.

**Keywords:** Face Recognition, Smart Attendance, Deep Learning, CNN, Automation

---

## INTRODUCTION

Introduction Attendance management is an integral part of every educational institution and organization. It helps in maintaining discipline, productivity, and accurate records. The conventional method of attendance management involves manual recording or ID cards, RFID, and biometric systems such as fingerprints. Although these systems are in wide use, they have some drawbacks such as time-consuming, prone to human error, and proxy attendance or manipulation of data. Recent developments in Artificial Intelligence (AI) and Machine Learning (ML) have made automated face recognition one of the most accurate and non-intrusive biometric identification methods. A Face Recognition-Based Smart Attendance System uses computer vision and pattern recognition algorithms to automatically identify and recognize faces from live video feeds or images. This technology employs OpenCV and deep learning algorithms to provide fast and accurate recognition, even in the presence of varying lighting and poses.

The purpose of this project is to create a system that reduces manual work, increases security, and boosts efficiency in the attendance management process. The inclusion of face recognition technology in the attendance system will enable institutions to promote transparency and eliminate the possibility of proxy or fake attendance. The primary aims of this project are to automate the attendance marking process, electronically record attendance, and offer real-time access to attendance information. The scope of this project includes schools, colleges, and office spaces where automated and accurate attendance management is necessary.

In addition, the use of automated attendance systems helps to improve resource planning and decision-making through accurate data on participation. Institutions of learning can use attendance analytics to understand engagement patterns, predict performance trends, and take corrective measures in instances of absenteeism. From a technological standpoint, there has been improvement in deep learning architectures that have improved the accuracy of face recognition.

## LITERATURE REVIEW

Current studies in intelligent educational environments combine face recognition with emotion analysis to automatically mark attendance and enhance classroom engagement. These solutions minimize administrative burdens while providing valuable information about students' well-being. Existing studies validate the effectiveness of combining biometric identification with behavioral analysis to optimize efficiency and facilitate data-driven learning environments. Deniz and Lee introduced a model that simultaneously monitors attendance and emotions to identify negative emotional anomalies. This model promotes early mental health awareness but also poses potential surveillance and bias issues. Likewise, Jha et al. developed a real-time face recognition attendance system that automates manual attendance marking. Although successful in a controlled setting, it is sensitive to lighting and partial occlusion. Kumar and Singh used convolutional neural networks for classroom emotion recognition to classify student

expressions and track engagement. Their research shows technical viability but relies too heavily on big data and may be susceptible to cultural interpretation bias. Zhang and Chen furthered this idea by proposing a comprehensive deep learning smart classroom framework that combines attendance and emotion tracking. While complete, their system is computationally intensive, making it difficult to scale.

More recent developments seek to address these issues and make the technology more deployable and privacy-friendly. Patel et al. (2024) developed an edge computing attendance system that locally processes facial data to minimize latency and ensure privacy. Wang et al. (2025) furthered this by developing a multimodal framework that combines facial, speech, and behavioural analysis to improve engagement tracking accuracy but raises new privacy concerns. The literature clearly shows the tremendous potential of intelligent attendance systems, but the issues of scalability, data diversity, computational complexity, and ethical management remain unaddressed. Future research must strike a balance between innovation and responsible AI use.

**Table 1. Comparative Analysis**

<b>Paper Title &amp; Authors</b>	<b>Concepts</b>	<b>Advantages</b>	<b>Disadvantages</b>
Computer Vision for Attendance and Emotion Analysis in School Settings (2023) – Sarah Deniz, Dakyung Lee	Uses face recognition for automated attendance and emotion analysis. Alerts when emotional state deviates negatively.	Saves teachers’ time; supports mental health monitoring; encourages ML adoption.	Possible emotion bias; privacy and ethical concerns.
Smart Attendance System Using Real-Time Face Recognition (2023) – Abhishek Jha et al.	Real-time facial recognition linked to attendance management.	Eliminates manual attendance; reduces proxy entries; improves efficiency.	Performance drops in poor lighting or partial face coverage.
Emotion Recognition from Student Facial Expressions in Classroom Environment (2023) – R. Kumar, P. Singh	CNN-based emotion detection to evaluate engagement.	Identifies disengaged or stressed students; improves teaching.	Needs large datasets; cultural bias risk.
Deep Learning-Based Automated Attendance and Emotion Detection in Smart Classrooms (2024) – L. Zhang, Y. Chen	Integrates deep learning for attendance and emotion monitoring.	Academic and psychological insights; smart classroom support.	High computational cost; strong infrastructure required.

## METHODOLOGY


### A. Architectural Overview

The system starts with image acquisition, where images of the classroom containing multiple students are taken using a camera module. The images undergo a multi-face detection process, where all the visible faces in the image are detected at once. The system is designed to handle multi-person environments, ensuring scalability for real-world classroom applications. After the detection process, a cropping and face selection module is used to isolate valid facial regions and eliminate rejected or low-quality face detections. This enhances the accuracy of face recognition by removing images of faces that are blurred or partially hidden. The subsequent process involves pre-processing and feature extraction, where normalized images of the faces are transformed into

numerical texture feature representations. The features used include unique identity patterns such as facial geometry and texture variations. A centralized database is used to store the pre-trained facial features of registered students. The extracted features from the live image are then matched with the stored features using classification algorithms.

The comparison step is used to determine whether a detected face matches a registered identity. The classification result triggers two decision paths:

- Match found → attendance marked present
- No match found → attendance marked absent



**Fig. 1: Block Diagram**

## B. Methodology

The proposed smart attendance system has been conceptualized as a multi-step computer vision system that can detect and recognize faces in real-time, automatically registering attendance.

**1.1 Face Detection:** A high-resolution camera is placed to capture a real-time video feed of the entire classroom environment. Face detection is applied to each video frame to identify facial regions of interest before recognition. A hybrid face detection method is used, which combines Haar-cascade classifiers for rapid initial screening with deep learning-based face detectors for enhanced robustness against varying lighting conditions, occlusions, and pose variations. This hybrid strategy enables effective face detection in real-world classroom settings.

**1.2 Feature Extraction:** Pre-processed facial regions are converted to grayscale, normalized, and resized to a fixed input size. Environmental noise due to lighting conditions is mitigated using illumination correction methods. A convolutional neural network (CNN) is used to extract distinctive facial features, which are then mapped to a compact embedding vector for each face. These embedding vectors encode identity-specific information that is robust to small variations in facial expressions and head pose.

**1.3 Face Recognition:** The resulting embeddings are then matched with the identity embeddings stored in a secure database. A classification system based on similarity, such as cosine similarity or Euclidean distance, identifies the most similar identity. If the similarity value is above a certain threshold, the identity is recognized and verified. Unrecognized faces are marked for administrative processing. This threshold-based recognition system ensures that there are few, if any, false positives.

**1.4 Attendance recording:** Once the identity has been successfully recognized, the attendance is automatically recorded with timestamps in a relational database. Session-level constraints ensure that there are no duplicate entries for the same person within a certain time frame. The system also enables automatic report generation, allowing instructors to view attendance analysis and participation data.

## C. Algorithm

The intelligent attendance system works through a series of automated steps that range from the capture of the classroom video to the recording of attendance. The system is intended to work in real-time with minimal human interaction.

### Step 1: Image Capture

A high-resolution camera captures live video from the classroom. The video is broken down into individual frames, and each frame is processed separately. This enables the system to track multiple students at once without any delay. The camera is positioned to capture the entire classroom, ensuring that the faces are visible even when the students shift slightly.

### Step 2: Face Detection using Haar Cascade

The algorithm scans each frame using the Haar Cascade classifier. The algorithm moves a detection window over the image at various scales. For each window, Haar features are assessed to see if the region is similar to a human face. The cascade is designed to quickly eliminate non-face regions in the early stages and thoroughly analyze regions of interest in the later stages. If a region successfully passes all stages, it is marked as a detected face and enclosed within a bounding box. Multiple faces can be detected in a single frame, enabling group attendance marking.

### Step 3: Face Cropping and Preprocessing

The face regions detected from the image are cropped and processed separately. The preprocessing steps include:

- a. Resizing to a fixed size
- b. Converting to grayscale
- c. Normalizing brightness and contrast
- d. Noise reduction

These steps ensure that the face images are standardized and ready for recognition by removing environmental factors.

#### Step 4: Feature Extraction

The preprocessed faces are then fed through a recognition algorithm (CNN or LBPH). The algorithm represents the face as a set of numbers called an embedding. The embedding is a digital signature of the face. It contains identity-specific information such as facial geometry and texture.

#### Step 5: Face Matching

The obtained embedding is matched with the existing embeddings in the student database. The matching is done using distance measures such as Euclidean distance or Cosine similarity. If similarity is above the threshold → identity confirmed. If similarity is below the threshold → unknown face. This step is used to ensure that the identity is confirmed accurately and no false matches occur.

#### Step 6: Attendance

Marking After the identity is confirmed:

- a. The student ID is obtained
- b. The current timestamp is recorded
- c. The attendance mark is stored in the database
- d. The rules for preventing duplication ensure that a student is not marked twice in a single session. If the face is not recognized, the system marks it for administrative purposes instead of attendance marking.

#### Step 7: Database Logging and Reporting

All the attendance information is stored in a database. The system is capable of automatically producing: Daily attendance reports, Monthly reports, Participation analysis, Absentee notifications. This removes the need for manual recording and the associated errors.

#### Step 8: Continuous Monitoring


The whole process is repeated for each frame in real-time. Late students can also be detected automatically. The process continues throughout the session.

## RESULT AND DISCUSSION

The proposed face recognition-based smart attendance system was tested on a dataset of registered participants captured under different environmental conditions, such as varying lighting intensities and orientations of the participants' faces. The dataset was created to represent real classroom environments to test the robustness and reliability of the system. The performance of the system was tested in terms of accuracy, response time, and system stability during real-time processing.

The experimental results show that the proposed system has a recognition accuracy of over 95, thus proving the system's efficiency in recognizing registered participants. The system performed well even when moderately occluded, for example, when the face is partially hidden or when the participant slightly turns his/her head.

In addition to accuracy, the response time analysis shows that the system is fast enough to be used in real classroom settings. The face detection and recognition processes take a few milliseconds per frame, ensuring smooth attendance registration without interrupting classroom activities. The automated logging system greatly minimized the number of false registrations compared to manual systems.



**Fig. 2: Face Recognition and Attendance Marking**

**Table 2: Result**

Metric Observation	Result	Observation
Recognition Accuracy	95.3\%	High identification reliability
Response Time	0.5 seconds	Suitable for real-time classroom use
False Attendance Rate	2.1\%	Reduced proxy and duplicate entries
Occlusion Robustness	Stable under moderate occlusion	Handles partial face coverage
Lighting Adaptability	High	Works under varied classroom lighting

### CONCLUSION

The Face Recognition-Based Smart Attendance System proves the effectiveness of artificial intelligence and computer vision in automating attendance management. The system uses facial recognition technology to mark attendance automatically, thus preventing proxy attendance and increasing the accuracy and efficiency of the attendance system. The use of machine learning algorithms such as LBPH or CNN helps the system recognize faces in real-time, even if the lighting conditions and background are different. The project helps to reduce human effort and upgrade the traditional attendance system to meet the modern digital requirements. Future improvements may include cloud storage and deep learning algorithms to increase the accuracy and scalability of the system.

### ACKNOWLEDGMENT

The author would also like to extend their sincere appreciation to the project guide and faculty members of the Department of Computer Engineering for their support and suggestions in the development of this research work. Their suggestions and inputs were very important in designing and developing the smart attendance system. The author would also like to thank the institution for providing the infrastructure and facilities required for conducting the experimentation process. The author would also like to thank the open-source developer community for providing the tools and resources such as OpenCV, Python libraries, and deep learning resources that helped accelerate the research process. The author would also like to thank their classmates and peers for their support and inputs in testing the system and making it more efficient. Finally, the author would like to thank their family members for their patience and support in completing this work.

### REFERENCES

1. S. Deniz and D. Lee, "Computer Vision for Attendance and Emotion Analysis in School Settings," Journal of Smart Education Systems, 2023.
2. A. Jha, R. Mehta, and S. Kulkarni, "Smart Attendance System Using Real-Time Face Recognition," International Journal of Computer Vision Applications, 2023.
3. R. Kumar and P. Singh, "Emotion Recognition from Student Facial Expressions in Classroom Environment," IEEE Access, 2023.
4. L. Zhang and Y. Chen, "Deep Learning-Based Automated Attendance and Emotion Detection in Smart Classrooms," IEEE Transactions on Learning Technologies, 2024.5
5. IEEE Transactions on Learning Technologies, 2024.5

6. N. Patel et al., "Edge-Based Intelligent Attendance and Emotion Analytics," 2024.
7. H. Wang et al., "Multimodal Student Engagement Detection," 2025.
8. H. Al-Nayyef, "Advancing Attendance: A Facial Recognition System Empowered by Deep Learning Techniques," *Journal of Al-Qadisiyah for Computer and Mathematics*, 2024.
9. S. Joshi, S. Shinde, P. Shinde, N. Sagar, and S. Rathod, "Facial Recognition Attendance System Using Machine Learning and Deep Learning," *IJERT*, vol. 12, no. 04, Apr. 2023.
10. A. Agustiyar, R. R. Isnanto, and C. E. Widodo, "Face Recognition for Attendance Systems: A Bibliometric Review of Research Trends and Opportunities," *SISFOCOM*, vol. 15, no. 01, Dec. 2025.
11. O. Oshin, J. Amenaghawon, F. Moninuola, and O. Idowu-Bismark, "Class Attendance System Using Facial Recognition," *International Journal of Intelligent Systems and Applications*, 2025.
12. Anshul, A. Kumar, and P. Behera, "Face Recognition Attendance Systems," *IJRASET*, 2025.
13. "AI-Powered Facial Recognition Attendance System Using Deep Learning and Computer Vision," *IJRSI*, vol. 12, no. 9, pp. 3902–3912, 2025.
14. M. Fikry, "Performance Analysis of Smart Technology with Face Detection using YOLOv3 and InsightFace for Student Attendance Monitoring," *International Journal of Intelligent Systems and Applications in Engineering*, 2024.
15. A. Nemavhola, C. Chibaya, and S. Viriri, "A Systematic Review of CNN Architectures and Databases," 2025.
16. P. Viola and M. Jones, "Rapid Object Detection Using a Boosted Cascade of Simple Features," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 511–518, 2001.
17. T. Ahonen, A. Hadid, and M. Pietikainen, "Face Recognition with Local Binary Patterns," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 28, no. 12, pp. 2037–2041, 2006.
18. M. Turk and A. Pentland, "Eigenfaces for Recognition," *Journal of Cognitive Neuroscience*, vol. 3, no. 1, pp. 71–86, 1991.
19. Y. Taigman, M. Yang, M. Ranzato, and L. Wolf, "DeepFace: Closing the Gap to Human-Level Performance in Face Verification," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1701–1708, 2014.
20. F. Schroff, D. Kalenichenko, and J. Philbin, "FaceNet: A Unified Embedding for Face Recognition and Clustering," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 815–823, 2015.
21. O. M. Parkhi, A. Vedaldi, and A. Zisserman, "Deep Face Recognition," *British Machine Vision Conference (BMVC)*, 2015.
22. I. Goodfellow, Y. Bengio, and A. Courville, "Deep Learning," MIT Press, 2016.
23. G. B. Huang, M. Ramesh, T. Berg, and E. Learned-Miller, "Labeled Faces in the Wild: A Database for Studying Face Recognition in Unconstrained Environments," University of Massachusetts, Amherst, Technical Report, 2007.
24. "AI-Powered Facial Recognition Attendance System Using Deep Learning and Computer Vision," *IJRSI*, vol. 12, no. 9, pp. 3902–3912, 2025.
25. M. Fikry, "Performance Analysis of Smart Technology with Face Detection using YOLOv3 and InsightFace for Student Attendance Monitoring," *International Journal of Intelligent Systems and Applications in Engineering*, 2024.
26. A. Nemavhola, C. Chibaya, and S. Viriri, "A Systematic Review of CNN Architectures and Databases," 2025.
27. P. Viola and M. Jones, "Rapid Object Detection Using a Boosted Cascade of Simple Features," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 511–518, 2001.
28. T. Ahonen, A. Hadid, and M. Pietikainen, "Face Recognition with Local Binary Patterns," *IEEE Transactions on Pattern Analysis and Machine Intelligence*, vol. 28, no. 12, pp. 2037–2041, 2006.
29. M. Turk and A. Pentland, "Eigenfaces for Recognition," *Journal of Cognitive Neuroscience*, vol. 3, no. 1, pp. 71–86, 1991.
30. Y. Taigman, M. Yang, M. Ranzato, and L. Wolf, "DeepFace: Closing the Gap to Human-Level Performance in Face Verification," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 1701–1708, 2014.
31. F. Schroff, D. Kalenichenko, and J. Philbin, "FaceNet: A Unified Embedding for Face Recognition and Clustering," *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 815–823, 2015.
32. O. M. Parkhi, A. Vedaldi, and A. Zisserman, "Deep Face Recognition," *British Machine Vision Conference (BMVC)*, 2015.
33. I. Goodfellow, Y. Bengio, and A. Courville, "Deep Learning," MIT Press, 2016.
34. G. B. Huang, M. Ramesh, T. Berg, and E. Learned-Miller, "Labeled Faces in the Wild: A Database for Studying Face Recognition in Unconstrained Environments," University of Massachusetts, Amherst, Technical Report, 2007.